

WG160128B Graphic 160x128dots

Dimension drawing $\textbf{129.0}\,\pm\,\textbf{0.5}$ 118.0 3.5 14.0 16.52 101.0(VA) 95.96(AA) 2.54 16.5max $\begin{array}{c} 2.9 \\ \hline 3.5 \\ \hline 7 \\ \hline 10.0 \\ \hline 13.12 \\ \end{array}$ 11.9 2.5 20- Ø 1.0 PTH 20- Ø 2.0 PAD 0.6 0.56 19 20 96.2 95.0 88.0 82.0(VA) 0.56 DOT SIZE SCALE 10/1 ععالم 5.0 1.6 4-ø3.5 57.5 57.0 4.0 122.0 3.5 LED B/L

- 1. Built in controller Tosiba- (T6963C or equivalent)
- 2.+5V power supply
- 3. 1/128 duty cycle
- 4. Optional N/V

-		AND MICHIGAN SECTION AND ADDRESS OF THE ADDRESS OF
Pin NO.	Symbol	Function
1	FG	Frame ground
2	Vss	Power supply(GND)
3	Vdd	Power supply (+5V)
4	Vadj	Contrast Adjustment
5	Vee	Negative Voltage output
6	WR	Data write
7	RD	Data read
8	CE	Chip enable
9	C/D	Command /data read/write
10	HALT	Clock operating stop signal
11	Reset	Reset signal
12	DB0	Data bus line
13	DB1	Data bus line
14	DB2	Data bus line
15	DB3	Data bus line
16	DB4	Data bus line
17	DB5	Data bus line
18	DB6	Data bus line
19	DB7	Data bus line
20	NC	No connection

Mechanical Data

Item	Standard Value	
Module Dimension	129.0x102.0	mm
Viewing Area	101.0x82.0	mm
Dot Size	0.56x0.56	mm
Dot pitch	0.60x0.60	mm
Mounting hole	122.0x96.2	mm

Absolute Maximum Rating

Item	Comment of	Stan	Llmit			
item	Symbol	min.	typ.	max.	Unit	
Power Supply	VDD-VSS	4.75	5.0	5.25	V	
Input Voltage	VI	-0.3		VDD	٧	

Note: VSS=0 Volt, VDD=5.0 Volt.

Electronical Characteristics

Albert Children Children Children Children								
Item	Symbol	Condition	Standard Value					
Item			min.	typ.	max.	Unit		
Innut Valtana	VDD	L level	0.7V _{DD}		VDD	٧		
Input Voltage	VIO	Hlevel	0		0.3V _{DD}	V		
Supply Current	IDD	VDD=+5V		45	50	mA		
		-20°C	19.9	21.0	22.1			
Recommended LC Driving		o°C	19.0		21.2			
Voltage for Normal Temp.	VDD-V0	25°C	18.6	19.1	19.6	v		
Version module		50°C	16.2	16.5	16.8			
		70°C	11.6	9.1	12.8			
CCFL Forward Voltage	VF	25°C		256	560	Vms		
CCFL Forward Current	IF	25°C			5.0	mA		
LED Forward Voltage	VF	25°C		4.6	4.6	٧		
LED Forward Current	IF v	el=110VA0 2450°F C			500	mA		

