


The non-specified tolerance of dimension is ± 0.15 mm.

PIN NO.	SYMBOL	PIN NO.	SYMBOL
26	DUTY1	1	NC
27	DUTY0	2	IRS
28	D7	3	/HPM
29	D6	4	P/S
30	D5	5	C86
31	D4	6	CLS
32	D3	7	M/S
33	D2	8	VR
34	D1	9	V0
35	D0	10	V4
36	/RD	11	V3
37	/WR	12	V2
38	A0	13	V1
39	/RES	14	NC
40	CS2	15	NC
41	/CS1	16	C2-
42	NC	17	C2+
43	/DOF	18	C1+
44	CL	19	C1-
45	FR	20	C3+
46	NC	21	NC
47	NC	22	VOUT
48	NC	23	VSS
49	NC	24	VDD2
		25	VDD

1	Lcd Type	FSTN White
2	Viewing Direction	6H
3	Drive Method	1/64 DUTY, 1/9 BIAS
4	Operating Voltage(LCD)	8.5V
5	Polirizer Mode	Positive Transflective
6	Operating Temperature	-20°C ~ 70°C
7	Storage Temperature	-30°C ~ 80°C



DOT SIZE
SCALE 10/1

SCALE:	3/2	REV:	
UNIT:	mm	PAGE:	1/1
APPROVE			
CHECK			
DRAW	黄晓伟 07/03/08		
MODEL		TITLE	
WX12864U-TFH#		LCM DRAWING	
DWG NO.		T-970711	

華凌光電股份有限公司
WINSTAR DISPLAY CO.