

SPU25B series

25W Desk Top Type
I.T.E. Power Supplies

Features:

- Wide Operating Voltage 90 to 264 VAC, 47 to 63 Hz
- IEC-320-C8 Input Inlet
- Optional Output Connector (See page appendix)
- Single Output
- Approved as Limited Power Source (LPS)
- Energy Star 2.0, Efficiency level V
- Class II
- 2 year warranty



Electrical Characteristics:

Vin	Safety Approvals Input Voltage Range	100~240VAC
	Operate Voltage Range	90~264VAC
fin	Input Frequency	47~63Hz
Po	Output Power Range	See rating chart
Vo	Output Voltage Range	See rating chart
Io	Output Current Range	See rating chart
Iil	Input Current (Low Line)	Io=Full load, Vin=100VAC 0.55A
Iih	Input Current (High Line)	Io=Full load, Vin=240VAC 0.30A
Ir	Low Line Inrush Current	Io=Full load, 25°C, Cool start, Vin=115VAC 25A (max.)
	High Line Inrush Current	Io=Full load, 25°C, Cool start, Vin=230VAC 50A (max.)
Eff	Efficiency	Io=Full Load, Vin=230VAC 75~95%
REG-i	Line Regulation	Io=Full Load 0.5~1%
REG-o	Load Regulation	Vin=230VAC 1~5%
OVP	Over Voltage Protection	Nil
OCP	Over Current Protection	110~150%
Ttr	Time of Transient Response	Io=Full Load to Half Load, Vin=100VAC 4mS (max.)
Th	Hold-Up Time	Io=Full Load, Vin=110VAC 12~16mS
Ts	Start Up Time	Io=Full Load, Vin=100VAC 2S (max.)
Vp-p	Ripple & Noise(Peak to Peak)	Full Load, Vin=90VAC 2% (max.)
Ilk	Leakage Current	Vin=240VAC/60Hz 0.25mA (max.)
TC	Temperature Coefficient	All output ±0.04%/°C
Pno	No-Load Power Consumption	No load, Vin=230VAC See rating chart
Vps	Dielectric Withstanding Voltage for Primary to secondary	Primary to secondary 4242VDC (min.)
Ris	Isolation Resistance	Test Voltage=500VDC 50MΩ (min.)

Application:

- POS System
- AV Equipment
- Industrial PC
- Note PC
- Charger
- LED Lighting

Safety Approvals:



UL/c-UL(UL 60950-1:2nd Edition)
TUV/GS(EN 60950-1:2nd Edition)

Environmental

To	Operating Temperature	See derating curve
Ts	Storage Temperature	-40~85°C
Ho	Operating Humidity	0~95%
Hr	Storage Humidity	0~95%
MTBF	Operating Temperature at 25°C, Calculated per MIL-HDBK-217F	0.3M Hrs (min.)
Pd	Derate linearly from 100% load at 40°C to 50% load at 70°C	




Http://www.sinpro.com

Http://www.sinpro.com.tw

Output Voltage And Current Rating Chart (Single Output) :

Model Number	Output Voltage	Output Current	Total Regulation	Max. Output Power	Pno (max.)
SPU25B-102	5 ~ 6 VDC	3.30 ~ 2.75 A	5%	16.5W	0.5W
SPU25B-103	6 ~ 8 VDC	3.33 ~ 2.50 A	5%	20W	0.5W
SPU25B-104	8 ~ 11 VDC	2.75 ~ 2.00 A	5%	22W	0.5W
SPU25B-105	11 ~ 13 VDC	2.27 ~ 1.92 A	5%	25W	0.3W
SPU25B-106	13 ~ 16 VDC	1.92 ~ 1.56 A	5%	25W	0.3W
SPU25B-107	16 ~ 21 VDC	1.56 ~ 1.19 A	5%	25W	0.3W
SPU25B-108	21 ~ 27 VDC	1.19 ~ 0.92 A	3%	25W	0.3W
SPU25B-109	27 ~ 33 VDC	0.92 ~ 0.75 A	3%	25W	0.3W
SPU25B-110	33 ~ 40 VDC	0.75 ~ 0.62 A	3%	25W	0.3W
SPU25B-111	40 ~ 48 VDC	0.62 ~ 0.52 A	3%	25W	0.3W


Mechanical Specifications:



Note:

1. Dimensions are shown in mm.
2. Weight: 170gs approx.
3. Optional output connector:
See page Appendix.

Derating Curve :



1. Operating Temperature: 0 to 70°C
2. Derate linearly from 100% load at 40°C to 50% load at 70°C