



MATERIAL:

NO	DESCRIPTION	MATERIAL	SUPPLIER	REMARK
1	CABLE	UL/CSA 2725 28AWG*1P+28AWG*2C +AB 65% JACKET;OD:3.5mm WHITE	GM	12-7046D1-07A
2	CONNECTOR	USB 3.1 "C" TYPE PLUG REV USB 2.0	YALIAN	*
3	CONNECTOR	MICRO USB 2.0 "B" TYPE PIN G/F SHELL NICKEL PLATED	YALIAN	24-005-097
4	PE	PE CLEAR	USIFE	41-001-034
5	PVC	PVC SHORE 88±2 COLOR:WHITE	GM	41-001-006
6	H. S. TUBE	HEAT SHRINK TUBE UL/CSA Ø1.0mm BLACK	WORE	42-A001001

PIN ASSIGNMENTS

P1	P2
A4, B4, A9, B9	VBUS 1
A6	Dp1 3
A7	Dn1 2
A1, B1, A12, B12	GND 5
SHELL	SHELL

NOTES:

- 1 100% OPEN&SHORT TEST
- 2 ALL MATERIALS IS RoHS COMPLIANCE

TOLERANCES			REVISIONS				COMPONENT NO :	
X .	+	mm	REV	DESCRIPTION	DATE	APPVD.	USB 2.0 TYPE C TO MICRO B L-IN WHITE	
X . X	-	mm	0	SAMPLE(MEUSB57010REV. 0)	JULY-07-15	LI	APPROVED :	
X . XX	+	mm					CHECKED :	TITLE : CABLE ASS' Y
X . XXX	-	mm						REQUIRED DOCUMENTS : *
								SCALE : / SHEET : 1 / 1 REV. 0
								DRAWN:Libo DRAWING : MEUSB57010
METRIC (mm)							DATE: JUNE-22-15	FILE:F:\SAMPLE\BJA57010. DWG
								THIRD ANGLE PROJECTION