



SENSITIVITY	感 度
SENSITIVITY REDUCTION	感度遞減
FREQUENCY	頻 率
MAX. WORKING VOLTAGE	最大工作電壓
CURRENT CONSUMPTION	電流消耗
S/N RATIO	信 噪 比
STORAGE TEMPERATURE	儲存溫度
WEIGHT	重 量

Schematic Diagram 測定電路圖

Dimensions (Unit: mm±0.2) 尺 寸 圖

Typical Frequency Response Curve 頻率響應圖

FEATURES

- Omnidirectional type
- Ultra thin
- For GSM, PDA....Dual Band applications

特色

- 全指向性
- 超薄
- 適用於GSM、PDA、雙頻機...等

OBO-63KA-0B

- $V_s=2.0V, R_L=2.2K\Omega$
- $-38\pm 3dB$ $-40\pm 3dB$ $-42\pm 3dB$ $-44\pm 3dB$
- $F=1KHz, 0dB=1V/Pa$
- Within $-3dB$ at $1.5V$ compare to $3.0V$
- $50\sim 16,000Hz$
- Max. $10V$
- Max. $0.5mA$
- More than $60dB$
- $-25^{\circ}C$ to $+70^{\circ}C$
- Max. $1.0gm$

OBO-63SC-0B

